

TECHNICAL SPECIFICATION OF OFFICE TABLE WITH DRAWER

1. Office table with drawer of steel frame manufactured by **ISO – 9001, ISO-14001/OHSAS CERTIFIED or BIFMA CERTIFIED** manufacturers.
2. **MATERIALS:** Frame should be made up of CRCA steel pipe/Sheets. Screws used shall be anodized wherever used. Table top should be made up of minimum 18mm thick MDF Board both side laminated conforming to ISI-14587 along with PVC beading all around the top.
3. Frame & Drawer should be duly powder coated.
4. **DIMENSIONS:** The dimensions of the table and table top shall be 1200mm X 750mm X 750mm ± 5 mm
5. **DRAWER BOX:** The drawer box shall consisting of three drawers be made from metal sheet not less than 0.8 mm thick. Minimum dimension of the Box should be width of the Box: 355mm; Height of the Box : 425mm; Depth of the Box : 565mm with maximum Tolerance: ± 5 mm
6. **DRAWER:** Drawer shall be made from CRCA sheet not less than 0.63 mm thick and shall have a slot and stopper strip of metal sheet at the rear, holding drawer in the box when it is fully opened./ Minimum dimension of the drawer: Width of the Drawer: 315mm; Height.: 125mm; Depth of the Drawer: 445 mm with maximum Tolerance: ± 5 mm. The lock shall not be less than six levers Brass-lock with duplicate keys of non-corrosive material. Each drawer shall be fitted with a built-in drawer pull system duly padded with a plastic cover
7. Drawer movement should be smooth based on channel type mechanism of good quality.
8. **TUBULAR FRAME:** The legs of the frame shall be made from CRCA 25 mm square steel tubular pipe (without joint) with a wall thickness of minimum 1.2 mm, welded/screwed to the main frame.
9. **FOOT REST:** Foot rest shall be made out of minimum 1.2 mm thick tubular pipe.
10. **FINISH:** All Dents. Burns and Sharp edges shall be removed from the various components. The components shall be individually pickled, scrubbed and rinsed to remove grease, rust scale or any other foreign element. Immediately after pickling, all the mild steel parts shall be given phosphate treatment. The finish should be smooth and uniform. The finish shall be free from all visible defects.

Other T&C

1. Minimum 1 year manufacturing defect guaranty i.e. fabric, welding, screws etc.
2. All tubular ends in table & chair should be covered with good quality rubber stopper.
3. Packing shall be of good quality to avoid damage or scratches during transit.
4. Color of item (frame & Fabric) shall be confirmed by ordering authority at the time of supply order or as per sample. Possible color options must be identified by bidder for various parts.
5. The final technical approval of furniture items shall be after inspection of samples by technical committee at the time of technical bid evaluation.
6. The Technical Committee or RMSCL representative may visit manufacturing unit any time during Rate Contract period on expenses of bidder.



Executive Director (EPM)
Rajasthan Medical Services Corporation Ltd.,
Jaipur