

SPECIFICATION OF OFFICE ALMIRAH

1. Almira (large) with adjustable shelves conforming to IS: 3312 manufactured by an ISO – 9001 & ISO-14001/ OHSAS 18001 CERTIFIED or BIFMA certified.

2. Material used: CRCA Sheet & anodized Screws.

3. DIMENSIONS

Height: 1980mm(1855+125) including the height of pedestals.

Width: 910mm

Depth: 480mm

No. of shelves: Four Numbers (adjustable)

Tolerances: ± 5 mm

4. FABRICATION

a. Sides, Back, Top and Bottom: The sides shall be made of Mild steel sheet of minimum 0.8mm thickness.

b. Supports: The adjustable shelves shall be supported on four adjustable brackets, resting on slotted MS Strips, fixed at four inside corners of almirah.

c. Doors: The steel Almira shall be provided with two doors formed out of mild steel sheet which shall have minimum 1mm thickness.

d. Pedestal: The pedestal shall also be made from mild steel sheet minimum 0.8mm

e. Hinges: The hinges shall be either plain butt type made from mild steel 1.6mm thick or double folded type fabricated from mild steel 1.2mm thick. The number of hinges on each door shall be three numbers.

5. Locking Mechanism: There shall be suitable locking mechanism not be less than six levers brass lock with duplicate keys of non corrosive material and three way bolting device.


Jan 12/22

chyo

6. Almirah should be duly powder coated as per ordered color or as per sample color.
7. FINISH: All Dents. Burns and Sharp edges shall be removed from the various components. The components shall be individually pickled, scrubbed and rinsed to remove grease, rust scale or any other foreign element. Immediately after pickling, all the mild steel parts shall be given phosphate treatment. The finish should be smooth and uniform. The finish shall be free from all visible defects.

Other T&C

1. Minimum 1 year manufacturing defect guaranty i.e. fabric, welding, Screws etc.
2. All tubular ends in table & chair should be covered with good quality rubber stopper.
3. Packing shall be of good quality to avoid damage or scratches during transit.
4. Color of item (frame & Fabric) will be confirmed by ordering authority at the time of supply order or as per sample. Possible color options must be identified by bidder for choice of user/purchaser.
5. The final technical approval of furniture items shall be after inspection of samples by technical committee at the time of technical bid evaluation.
6. The Technical Committee or RMSCL representative may visit manufacturing unit any time during Rate Contract period.
7. The RMSCL may do pre dispatch inspection at supplier store/ premises/ factory.



Executive Director (EPM)
Rajasthan Medical Services Corporation Ltd.,
Jaipur

