TECHNICAL SPECIFICATIONS OF LIBRARY CABINET (STEEL) WITH GLASS DOOR

1. Library Cabinet (Steel) with Glass Door standard covers requirements of materials, construction and finish of Toughened Glass with adjustable shelves from ISO - 9001, ISO- 14001/OHSAS CERTIFIED or BIFMA CERTIFIED manufacturers only.

2. **DIMENSIONS:**

The dimensions of Library Glass Door Cabinet shall:

Height:

1800mm

Width:

900mm

Depth:

375mm

No. of shelves: Four Numbers (adjustable)

Tolerances:

+ 5mm

- 3. MATERIALS: Should be Mild Steel Sheets wherever used shall be CRCA and screws shall be anodized.
- 4. Cabinet Sides, Back, Top and Bottom shall be made of Mild steel sheet 0.8mm thickness.
- 5. The adjustable shelves shall be supported on four adjustable brackets, resting on slotted MS Strips, fixed at four inside corners of Cabinet.
- 6. The Glass Door Cabinet shall be provided with two doors, fitted with Toughened Glass, formed out of mild steel sheet which shall have 1mm thickness.
- The pedestal shall also be made from mild steel sheet 0.8mm.
- 8. The hinges shall be either plain butt type made from mild steel 1.6mm thick or double folded type fabricated from mild steel 1.2mm thick.
- 9. The number of hinges on each door shall be three numbers. There shall be suitable locking mechanism not be less than six levers brass lock with duplicate keys of non corrosive material and three way bolting device controlled by zinc based alloy handle.
- 10. All Metal Parts shall be powder coated and screws shall be anodized.
- 11. FINISH: All Dents. Burns and Sharp edges shall be removed from the various components. The components shall be individually pickled, scrubbed and rinsed to remove grease, rust scale or any other foreign element.

Other T&C

- 1. Minimum 1 year manufacturing defect guaranty i.e. fabric, welding, screws etc.
- All tubular ends in table & chair should be covered with good quality rubber stopper.
- 3. Packing shall be of good quality to avoid damage or scratches during transit.
- 4. Color of item (frame & Fabric) shall be confirmed by ordering authority at the time of supply order or as per sample. Possible color options must be identified by bidder for various parts.
- The final technical approval of furniture items shall be after inspection of samples by technical committee at the time of technical bid evaluation.

The Technical Committee or RMSCL representative may visit manufacturing unit any time during Rate Contract period on expenses of bidder.

Executive Director (EPM) Rajasthan Medical Services Corporation Ltd., Jaipur