

TECHNICAL SPECIFICATIONS FOR OFFICE ALMIRAH (SMALL)

1. Almirah (small) with adjustable shelves conforming to IS: 3312 /1984 **ISO – 9001, ISO-14001/OHSAS CERTIFIED or BIFMA CERTIFIED** manufacturers only.

2. Materials used: CRCA sheet and anodized screws.

3. DIMENSIONS

The dimensions of Almirah (small) shall conform to IS 3312 / 1984.

Height	:	1280mm including the height of pedestals (pedestals height should be 125mm ±5mm).
Width	:	765mm
Depth	:	430mm
No. of shelves	:	Three Numbers (adjustable)
Tolerances	:	± 5mm

4. FABRICATION

- a. Sides, Back, Top and Bottom shall be made of Mild steel CRCA sheet 0.8mm thickness.
 - b. **Supports:** The adjustable shelves shall be supported on four adjustable brackets, resting on slotted MS Strips, fixed at four inside corners of almirah.
 - c. **Doors:** The steel Almirah shall be provided with two doors formed out of mild steel CRCA sheet which shall have 1mm thickness.
 - d. Pedestal shall also be made from mild steel CRCA sheet 0.8mm
 - e. Hinges shall be either plain butt type made from mild steel 1.6mm thick or double folded type fabricated from mild steel 1.2mm thick The number of hinges on each door shall be three numbers.
5. **Locking Mechanism:** There shall be suitable locking mechanism not be less than six levers brass lock with duplicate keys of non corrosive material and three way bolting device .
 6. All metal parts shall be powder coated and screws used should be anodized.
 7. **FINISH:** All Steel components shall be free from dents, burs and sharp edges. The components shall be individually picked, scrubbed and rinsed to remove grease, rust, scale or any other foreign element. The finish should be smooth and uniform. The finish shall be free from all visible defects.

Other T&C

1. Minimum 1 year manufacturing defect guaranty i.e. fabric, welding, screws etc.
2. All tubular ends in table & chair should be covered with good quality rubber stopper.
3. Packing shall be of good quality to avoid damage or scratches during transit.
4. Color of item (frame & Fabric) shall be confirmed by ordering authority at the time of supply order or as per sample. Possible color options must be identified by bidder for various parts.
5. The final technical approval of furniture items shall be after inspection of samples by technical committee at the time of technical bid evaluation.
6. The Technical Committee or RMSCL representative may visit manufacturing unit any time during Rate Contract period on expenses of bidder.



Executive Director (EPM)
Rajasthan Medical Services Corporation Ltd.,
Jaipur