

TECHNICAL SPECIFICATION

Automatic Scrubber Drier

1. It should be mains operated 230V- 250 V/ 50 Hz.
2. It should have high degree of maneuverability.
3. It must do optimum vacuuming of dirt water even in corners.
4. It should be non corrosive.
5. The working width should be 600mm \pm 50mm.
6. The effective suction width should be 850 mm \pm 50mm.
7. The working speed should be 4 km/hr \pm .5 km/hr.
8. The vacuum pressure should be 80 mm Hg \pm 10 mm Hg..
9. No. of Brushes should be either one or two.
10. The total diameter of brushes should be 600 mm \pm 50 mm.
11. The brush speed should be 180 rpm \pm 20rpm.
12. The dirt water tank capacity should be 60 ltrs \pm 5 ltrs.
13. The fresh water tank capacity should be 60 ltrs \pm 5 ltrs.
14. The noise level should be \leq 70 db.
15. The supply cable length should be \geq 25 mtrs.
16. Consumable: Brush and Rubber Lips, squeazy only.

General Terms And Condition

1. Guarantee of the complete System should be of two years. CMC will be given @ 6% (of net rate-inclusive of Excise Duty & exclusive of VAT/CST etc.) plus service tax (as applicable) and yearly escalation of 5 % on last year's CMC price. The rates of CMC may be awarded for five years after guarantee of two years.
2. All the equipment should be FDA/CE approved and the supplier should be ISO Certified.



Executive Director (EPM)

**Rajasthan Medical Services Corporation Ltd,
Jaipur**